

V 51°15'60.0"N
5°34'59.99"E

THE 100% ELECTRIC ALL-ROUNDER

AGRIMAC TE17/4



43°11'17.3"N
2°41'09.0"W V

MAKE WORK AN ADVENTURE

> 51°15'60.0"N
5°34'59.99"E

Benefits

- Ⓢ 100% electric
- Ⓢ Easy to recharge
- Ⓢ Only 136 cm wide
- Ⓢ Little need for periodic maintenance

About the AGRIMAC TE17

Whether it's festivals, construction sites, fruit growing or other intensive jobs, the Agrimac TE17-4 can handle it all. With a lifting capacity of 1,700 kg, it is versatile and always reliable, whether you're moving light and sound equipment, clearing materials or transporting harvest crates.

Thanks to the lithium-ion battery with built-in plug, charging is quick and easy. The plug-and-play system keeps downtime to a minimum, so you can work when it suits you. In addition, the Curtis controller provides extra security by detecting malfunctions at an early stage, minimising maintenance and preventing unexpected downtime.

With a width of only 136 cm and a turning circle of 4.00 m, the TE17 manoeuvres effortlessly between tents, trees or machines. This makes it not only useful at festivals or on construction sites, but also particularly suitable for orchards, greenhouses and narrow paths in agriculture. Its robust design and high reliability ensure that it continues to perform even under the toughest conditions, on rough terrain and in bad weather.

That is why Agrimac rough terrain forklifts are considered the most reliable choice by professionals in a wide range of sectors.

So turn your work into an adventure and choose the 100% electric Agrimac TE17!

Specifications

Capacity	1.700 kg
Weight	3.500 kg
Engine	CFR
Power	28.0 kW
Emission standard	Zero emissions
Propulsion	Linde pump combined with Poclairn multi-engine
Traction	4x4
Speed	Up to 18 km/h
Inclines up to	35%
Turning radius	External: 4.00 m Internal: 2.05 m
Brakes	<ul style="list-style-type: none">• Hydrostatic on all wheels• Disc brakes on front wheels• Automatic four-wheel hydraulic braking system
Wheels	Front: 10.0/75-15,3" Rear: 7.0/12"
Transmission	Wheel motor
Displacement pump: Flow	120 l/min
Displacement pump: Pressure	400 bar
Tank capacity: Oil	35 l
Battery	100 V / 300 Ah
Battery brand	BSL
Charger	100 V
Charger brand	ATIP
Maat options	Duplex: 2.50 m / 3.14 m / 3.60 m Triplex: 3.00 m / 3.80 m / 4.00 m

43°11'17.3"N >
2°41'09.0"W

AGRIMAC

Barrio de Euba, Amorebieta
48340, Vizcaya, Spain
construccion@agrimac.es

MAKE WORK AN ADVENTURE